

[illegible]

```
RRRRRRRR  UU      UU  NN      NN  DDDDDDDD  EEEEEEEEE  TTTTTTTTTT
RRRRRRRR  UU      UU  NN      NN  DDDDDDDD  EEEEEEEEE  TTTTTTTTTT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RRRRRRRR  UU      UU  NN      NN  DD      DD  EE      TT
RRRRRRRR  UU      UU  NN      NN  DD      DD  EEEEEEEE  TT
RR      RR  UU      UU  NN      NN  DD      DD  EEEEEEEE  TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UU      UU  NN      NN  DD      DD  EE      TT
RR      RR  UUUUUUUUU  NN      NN  DDDDDDDD  EEEEEEEEE  TT
RR      RR  UUUUUUUUU  NN      NN  DDDDDDDD  EEEEEEEEE  TT
```

```
....
....
....
....
```

```
LL      IIIIII  SSSSSSSS
LL      IIIIII  SSSSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SSSSSS
LL      II      SSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LLLLLLLLLL  IIIIII  SSSSSSSS
LLLLLLLLLL  IIIIII  SSSSSSSS
```



```
0001 0 MODULE rundet (XTITLE 'Run Detached Process -- CLI Utility Procedure'
0002 0 IDENT = 'V04-000',
0003 0 MAIN = run_detached) =
0004 1 BEGIN
0005 1
0006 1 *****
0007 1 *
0008 1 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0009 1 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0010 1 * ALL RIGHTS RESERVED.
0011 1 *
0012 1 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0013 1 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0014 1 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0015 1 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0016 1 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0017 1 * TRANSFERRED.
0018 1 *
0019 1 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0020 1 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0021 1 * CORPORATION.
0022 1 *
0023 1 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0024 1 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0025 1 *
0026 1 *
0027 1 *****
0028 1
0029 1 ++
0030 1
0031 1 Facility:
0032 1
0033 1 CLI Utility
0034 1
0035 1 Abstract:
0036 1
0037 1 This module contains the routines necessary to act as a CLI interface
0038 1 to the create process ($CREPRC) and schedule wakeup ($SCHDWK) system
0039 1 services.
0040 1
0041 1 Environment:
0042 1
0043 1 VAX/VMS User Mode, Non-Privileged
0044 1
0045 1 Author:
0046 1
0047 1 Michael T. Rhodes, Creation Date: March, 1983
0048 1
0049 1 Modified By:
0050 1
0051 1 V03-007 MCN0159 Maria del C. Nasr 28-Mar-1984
0052 1 Use LIB$TPARSE to parse uic instead of RUN_CVTUIC.
0053 1
0054 1 V03-006 RAS0274 Ron Schaefer 20-Mar-1984
0055 1 Make this work with searchlists by using LIB$FIND FILE
0056 1 to parse the image filespec. Wildcards are not allowed.
0057 1
```

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure

M 12
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 2
(1)

:	58	0058	1	:	V03-005	TMK0001	Todd M. Katz	13-Nov-1983
:	59	0059	1	:			Add the qualifier /JOB_TABLE_QUOTA. The use of this	
:	60	0060	1	:			qualifier allows the creator of a detached process to	
:	61	0061	1	:			specify its job-wide logical name table creation quota.	
:	62	0062	1	:				
:	63	0063	1	:	V03-004	MTR0002	Michael T. Rhodes	22-Jul-1983
:	64	0064	1	:			Correct qualifier name /PROCESS to /PROCESS_NAME.	
:	65	0065	1	:				
:	66	0066	1	:	V03-003	MTR0001	Michael T. Rhodes	29-Apr-1983
:	67	0067	1	:			Convert privilege processing to use common CLI utility	
:	68	0068	1	:			routine PRV\$SETPRIV. Also change PID message to PROC_ID.	
:	69	0069	1	:				
:	70	0070	1	:	V03-002	WMC0002	Wayne Cardoza	14-Apr-1983
:	71	0071	1	:			Qualifier is /DETACHED	
:	72	0072	1	:				
:	73	0073	1	:	V03-001	WMC0001	Wayne Cardoza	11-Apr-1983
:	74	0074	1	:			Add /DETACH and /DUMP flags.	
:	75	0075	1	:				
:	76	0076	1	:				
:	77	0077	1	:				


```
79 0078 1 %SBTTL 'Declarations'
80 0079 1
81 0080 1   Include Files:
82 0081 1
83 0082 1   LIBRARY 'SYSS$LIBRARY:LIB';
84 0083 1   LIBRARY 'SYSS$LIBRARY:TPAMAC';
85 0084 1
86 0085 1
87 0086 1   Table of Contents:
88 0087 1
89 0088 1 FORWARD ROUTINE
90 0089 1   run_detached      : NOVALUE,
91 0090 1   init_arg_list    : NOVALUE,
92 0091 1   parse_image_spec : NOVALUE,
93 0092 1   get_wakeup_info  : NOVALUE,
94 0093 1   get_uic         : NOVALUE,
95 0094 1   get_privileges  : NOVALUE,
96 0095 1   get_quotas     : NOVALUE,
97 0096 1   get_cpulm       : NOVALUE,
98 0097 1   get_value      : NOVALUE,
99 0098 1   insert_quota   : NOVALUE,
100 0099 1   get_stsflgs    : NOVALUE,
101 0100 1   schedule_process : NOVALUE;
102 0101 1
103 0102 1
104 0103 1   External references:
105 0104 1
106 0105 1 EXTERNAL ROUTINE
107 0106 1   CLISGET VALUE      : ADDRESSING_MODE (GENERAL),
108 0107 1   CLISPRESNT      : ADDRESSING_MODE (GENERAL),
109 0108 1   lib$cvdt_time    : ADDRESSING_MODE (GENERAL),
110 0109 1   LIB$CVT_DX_DX     : ADDRESSING_MODE (GENERAL),
111 0110 1   lib$cvt_time    : ADDRESSING_MODE (GENERAL),
112 0111 1   LIB$GET_VM      : ADDRESSING_MODE (GENERAL),
113 0112 1   LIB$FIND_FILE   : ADDRESSING_MODE (GENERAL),
114 0113 1   LIB$TPARSE     : ADDRESSING_MODE (GENERAL),
115 0114 1   prv$setpriv    : ADDRESSING_MODE (GENERAL);
116 0115 1
117 0116 1
118 0117 1   Define message codes...
119 0118 1
120 P 0119 1 $SHR_MSGDEF (RUN,192,GLOBAL,
121 P 0120 1 (INSVIRMEM,SEVERE),
122 P 0121 1 (INVQUAVAL,ERROR),
123 P 0122 1 (PARSEFAIL,SEVERE),
124 0123 1 (SYNTAX,SEVERE));
125 0124 1
126 0125 1 EXTERNAL LITERAL
127 0126 1   cli$_negated,
128 0127 1   run$_creprc,
129 0128 1   run$_proc_id,
130 0129 1   run$_getjpi,
131 0130 1   run$_cyterr,
132 0131 1   run$_invaic,
133 0132 1   run$_illval,
134 0133 1   run$_schdwk;
135 0134 1
```

! Define VMS structures.
! T\$PARSE structures

! Create a sub or detached process.
! Initialize the \$CREPRC and \$SCHDWK argument lists.
! Obtain the expanded image file specification.
! Get info for the \$SCHDWK.
! Get the UIC value.
! Set up the privilege mask vector for the process.
! Set up the quota list for the process.
! Special case for CPU time limit quota.
! Get the value of the current command line entity.
! Insert a quota list entry.
! Set up the initial process status flag vector.
! Schedule the process to be executed.

! CLI call back routine to get command line entity.
! CLI call back routine to determine entity presence
! Private CLI routine to convert a string to a delta
! General conversion routine.
! Private CLI routine to convert a string to an abso
! Library routine to obtain virtual memory.
! Library routine to parse filespecs.
! Table driven parser
! Private CLI routine to process privileges and set

! Define the shareable messages first.
! Insufficient virtual memory.
! Invalid qualifier value.
! Error parsing file spec.
! Error parsing command entity.

! Command line entity was explicitly negated.
! Create process failed.
! Identification of created process.
! Error obtaining job and process information.
! Error converting entity value.
! Invalid UIC.
! Illegal CPU time limit.
! Failed to schedule the wakeup request.

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
Declarations

B 13
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 4
(2)

: 136

0135 1


```
138 0136 1 %SBTTL 'Declarations -- Private Storage'
139 0137 1
140 0138 1 Command qualifiers, keywords, and keyword paths
141 0139 1
142 0140 1 BIND
143 0141 1 accounting = $descriptor ('ACCOUNTING'),
144 0142 1 authorize = $descriptor ('AUTHORIZE'),
145 0143 1 delay = $descriptor ('DELAY'),
146 0144 1 detach = $descriptor ('DETACHED'),
147 0145 1 dump = $descriptor ('DUMP'),
148 0146 1 error = $descriptor ('ERROR'),
149 0147 1 input = $descriptor ('INPUT'),
150 0148 1 interval = $descriptor ('INTERVAL'),
151 0149 1 mailbox = $descriptor ('MAILBOX'),
152 0150 1 output = $descriptor ('OUTPUT'),
153 0151 1 p1 = $descriptor ('P1'),
154 0152 1 priority = $descriptor ('PRIORITY'),
155 0153 1 privileges = $descriptor ('PRIVILEGES'),
156 0154 1 process = $descriptor ('PROCESS NAME'),
157 0155 1 resource_wait = $descriptor ('RESOURCE_WAIT'),
158 0156 1 schedule = $descriptor ('SCHEDULE'),
159 0157 1 service_fail = $descriptor ('SERVICE_FAILURE'),
160 0158 1 swapping = $descriptor ('SWAPPING'),
161 0159 1 uic = $descriptor ('UIC');
162 0160 1
163 0161 1 LITERAL
164 0162 1 true = 1, false = 0,
165 0163 1 jpientries = 3,
166 0164 1 jpilistsize = jpientries * 12,
167 0165 1 list_k_entry_size = 5,
168 0166 1 priv_entries = 31;
169 0167 1
170 0168 1 MACRO
171 0169 1 list_entry (name, entity) = BYTE (name), LONG ($descriptor (entity)) %,
172 0170 1 list_b_name = 0,0,8,0 %,
173 0171 1 list_l_value = 1,0,32,0 %;
174 0172 1
175 0173 1 OWN
176 0174 1 run$a_error : $bblock [dsc$c_s_bln],
177 0175 1 run$a_image : $bblock [dsc$c_s_bln],
178 0176 1 run$a_input : $bblock [dsc$c_s_bln],
179 0177 1 run$a_input_desc : $bblock [dsc$c_s_bln],
180 0178 1 run$a_output : $bblock [dsc$c_s_bln],
181 0179 1 run$a_prcnam : $bblock [dsc$c_s_bln],
182 0180 1 run$a_quota,
183 0181 1 run$l_baspri,
184 0182 1 run$l_mbxunt,
185 0183 1 run$l_pid,
186 0184 1 run$l_status,
187 0185 1 run$l_stsflg : $bblock [4],
188 0186 1 run$l_uic,
189 0187 1 run$q_daytim : VECTOR [2, LONG] INITIAL (-1,-1),
190 0188 1 run$q_interval : VECTOR [2, LONG] INITIAL (0,0),
191 0189 1 run$q_privadr : VECTOR [2, LONG],
192 0190 1 run$a_image_buf : $bblock [nam$c_maxrss],
193 0191 1 run$a_findfile : ref $bblock,
194 0192 1
```

Log accounting records for created process
Perform user authorization when image is L
Hibernate process and awaken after delta t
Detached process
Image dump requested
Error device (SY\$ERROR).
Input device (SY\$INPUT).
Hibernate process and awaken at regularly
Unit number of termination mailbox for thi
Output device (SY\$OUTPUT).
Image file specification parameter.
Base priority at which the created process
Defines the privileges for the created pro
Specifies the process name.
Enable/disable resource wait mode for the
Hibernate the process and awaken at absolu
Enable/disable system service failure exce
Enable/disable process swapping.
Detached process UIC.

Boolean operands.
Number of entries in the \$GETJPI item list
Number of bytes required for the \$GETJPI i
Number of bytes in a list entry.
Number of real privileges (prv\$v_xxx).

Macro to create list entries for the quota
Name field access formal.
Value field access formal.

Descriptor for error device specification.
Descriptor for image file specification.
Descriptor for input device specification.
General purpose dynamic input descriptor.
Descriptor for output device specification
Descriptor for process name.
Quota list head address.
Base execution priority for the process.
Termination mailbox unit number.
Created process' PID.
Global Status vector.
Initial process state status flags.
Detached process' UIC.
Time at which the process is to be awakene
Interval at which the wake up request is t
Privilege vector.
Buffer to hold the expanded file specifica
Context ptr for LIB\$FIND_FILE.

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
Data Structures -- \$GETJPI Item List

D 13
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.832;1

Page 6
(4)

```
: 196      0193 1 %SBTTL 'Data Structures -- $GETJPI Item List'
: 197      0194 1 ++
: 198      0195 1
: 199      0196 1 Functional Description:
: 200      0197 1
: 201      0198 1 This structure is used to obtain default job and process information
: 202      0199 1 for the created process.
: 203      0200 1
: 204      0201 1 --
: 205      0202 1 run$a_getjpi : $bblock [jpilistsize]                                ! Item list for $GETJPI.
: 206      0203 1 INITIAL (
: 207      0204 1 WORD (4, jpi$_prib), LONG (run$a_baspri, 0), ! Process base priority.
: 208      0205 1 WORD (8, jpi$_procpriv), LONG (run$a_prvadr, 0), ! Process 'SAME' privileges.
: 209      0206 1 WORD (0, 0), LONG (0, 0), ! Item list terminator.
: 210      0207 1
```



```
212 0208 1 %SBTTL 'Data Structures -- Quota Table'
213 0209 1 ++
214 0210 1
215 0211 1 Functional Description:
216 0212 1
217 0213 1 This structure is used to parse and process the command line entries
218 0214 1 which comprise the quota list values and to establish the initial quota
219 0215 1 context for the $CREPRC system service.
220 0216 1
221 0217 1 --
222 0218 1 run$a_quota_tbl : $bblock [(pql$_length - 1) * list_k_entry_size]
223 0219 1 INITIAL (
224 0220 1 list_entry (pql$_astlm, 'AST LIMIT'),
225 0221 1 list_entry (pql$_bytlm, 'BUFFER LIMIT'),
226 0222 1 list_entry (pql$_enqlm, 'ENQUEUE LIMIT'),
227 0223 1 list_entry (pql$_wsextent, 'EXTENT'),
228 0224 1 list_entry (pql$_fillm, 'FILE LIMIT'),
229 0225 1 list_entry (pql$_biolm, 'IO_BUFFERED'),
230 0226 1 list_entry (pql$_diolm, 'IO_DIRECT'),
231 0227 1 list_entry (pql$_wsquota, 'MAXIMUM WORKING_SET'),
232 0228 1 list_entry (pql$_pgflquota, 'PAGE FILE'),
233 0229 1 list_entry (pql$_tqelm, 'QUEUE LIMIT'),
234 0230 1 list_entry (pql$_prclm, 'SUBPROCESS LIMIT'),
235 0231 1 list_entry (pql$_cpulm, 'TIME LIMIT'),
236 0232 1 list_entry (pql$_wsdefault, 'WORKING SET'),
237 0233 1 list_entry (pql$_jtquota, 'JOB_TABLE_QUOTA')
238 0234 1 );
239 0235 1
240 0236 1 ! TPARSE state table to parse the uic value
241 0237 1 !
242 0238 1
243 0239 1 $INIT_STATE ( uic_states, uic_keys );
244 0240 1
245 P 0241 1 $STATE (,
246 P 0242 1 (tpa$_ident,...,run$l_uic)
247 0243 1 );
248 0244 1
249 P 0245 1 $STATE (,
250 P 0246 1 (tpa$_eos, tpa$_exit)
251 0247 1 );
```

! Quota table.

! AST limit quota.

! Maximum number of bytes fo

! Maximum # of outstanding l

! Max size to which an image

! Maximum number of simultan

! Max number of concurrent b

! Maximum number of concurre

! Max size which process can

! Max number of pages alloca

! Maximum number of timer qu

! Max number of subprocesses

! Maximum CPU time allocated

! Default working set size f

! Job-wide logical name tabl

```
0248 1 %SBTTL 'run_detached -- Create a sub or detached process'
0249 1 ROUTINE run_detached : NOVALUE =
0250 1 ++
0251 1
0252 1 Functional Description:
0253 1
0254 1 This routine is responsible for calling the initialization procedure
0255 1 which will build the argument lists used for performing the create
0256 1 process ($CREPRC) system service. If the process is to be scheduled
0257 1 to be awakened or re-executed at specific intervals, a call is made
0258 1 to perform that action.
0259 1
0260 1 Implicit Inputs:
0261 1
0262 1 The command line supplied by the CLI.
0263 1
0264 1 Implicit Outputs:
0265 1
0266 1 The process is created with the process identification (PID) of the
0267 1 created process SIGNALled to the caller as a success status message.
0268 1
0269 1 Routine Value:
0270 1
0271 1 SSS_NORMAL Process was created/scheduled without errors.
0272 1
0273 1 false Error status from failed routine.
0274 1
0275 1 Side Effects:
0276 1
0277 1 The process may have been hibernated with a scheduled wake up pending.
0278 1
0279 1 --
0280 2 BEGIN
0281 2
0282 2 init_arg_list (); ! Initialize the argument lists for the $CREPRC and
0283 2
0284 2 IF NOT (run$l_status = $CREPRC (PIDADR = run$l_pid, ! Process ID of created process.
0285 2 IMAGE = run$a_image, ! File specification of the image to execute.
0286 2 INPUT = run$a_input, ! Input device specification (assigned to SYSS$INPUT)
0287 2 OUTPUT = run$a_output, ! Output device specification (assigned to SYSS$OUTPU
0288 2 ERROR = run$a_error, ! Error device specification (assigned to SYSS$ERROR)
0289 2 PRIVADR = run$g_privadr, ! Quadword privilege vector address.
0290 2 QUOTA = .run$a_quota, ! List head address for the quota list.
0291 2 PRCNAM = run$a_prcnam, ! Process name.
0292 2 BASPRI = .run$l_baspri, ! Process base execution priority.
0293 2 UIC = .run$l_uic, ! Process UIC.
0294 2 MBXUNT = .run$l_mbxunt, ! Termination mailbox unit number.
0295 2 STSFLG = .run$l_stsflg)) ! Initial process state status flags.
0296 2
0297 2 THEN SIGNAL_STOP (run$creprc, 0, .run$l_status) ! Any errors, stop here and inform the user.
0298 2 ELSE
0299 2 SIGNAL (run$proc_id, 1, .run$l_pid); ! Process was created successfully, show it's PID to
0300 2
0301 2 IF .run$l_stsflg [prc$u_hiber] ! Should we leave a wake up call?
0302 2 THEN schedule_process ();
0303 2
0304 1 END; ! of ROUTINE run_detached
```



```

:
.TITLE RUNDET Run Detached Process -- CLI Utility Proc
.IDENT \V04-000\
.PSECT _LIB$STATES,NOWRT, SHR, PIC,1
00000 UIC_STATES::
45EC 00000 ;TPASTYPE .BLKB 0
00000000* 00002 U.2: .WORD 17900
15F7 00006 U.3: .LONG <<RUNSL_UIC-U.3>-4>
FFFF 00008 U.4: .WORD 5623
;TPASTARGET U.5: .WORD -1
.PSECT _LIB$KEYOS,NOWRT, SHR, PIC,1
00000 UIC_KEYS::
00000 ;TPASKEY0 U.1: .BLKB 0
.PSECT $SPLITS,NOWRT,NOEXE,2
47 4E 49 54 4E 55 4F 43 43 41 00000 P.AAB: .ASCII \ACCOUNTING\
0000A .BLKB 2
00000000A 0000C P.AAA: .LONG 10
000000000 00010 .ADDRESS P.AAB
45 5A 49 52 4F 48 54 55 41 00014 P.AAD: .ASCII \AUTHORIZE\
0001D .BLKB 3
000000009 00020 P.AAC: .LONG 9
000000000 00024 .ADDRESS P.AAD
59 41 4C 45 44 00028 P.AAF: .ASCII \DELAY\
0002D .BLKB 3
000000005 00030 P.AAE: .LONG 5
000000000 00034 .ADDRESS P.AAF
44 45 48 43 41 54 45 44 00038 P.AAH: .ASCII \DETACHED\
000000008 00040 P.AAG: .LONG 8
000000000 00044 .ADDRESS P.AAH
50 4D 55 44 00048 P.AAJ: .ASCII \DUMP\
000000004 0004C P.AAI: .LONG 4
000000000 00050 .ADDRESS P.AAJ
52 4F 52 52 45 00054 P.AAL: .ASCII \ERROR\
00059 .BLKB 3
000000005 0005C P.AAK: .LONG 5
000000000 00060 .ADDRESS P.AAL
54 55 50 4E 49 00064 P.AAN: .ASCII \INPUT\
00069 .BLKB 3
000000005 0006C P.AAM: .LONG 5
000000000 00070 .ADDRESS P.AAN
4C 41 56 52 45 54 4E 49 00074 P.AAP: .ASCII \INTERVAL\
000000008 0007C P.AAO: .LONG 8
000000000 00080 .ADDRESS P.AAP

```

58	4F	42	4C	49	41	4D	00084	P.AAR:	.ASCII	\MAILBOX\	:
							0008B		.BLKB	1	:
							00000007	P.AAQ:	.LONG	7	:
							00000000		.ADDRESS	P.AAR	:
54	55	50	54	55	4F		00094	P.AAT:	.ASCII	\OUTPUT\	:
							0009A		.BLKB	2	:
							00000006	P.AAS:	.LONG	6	:
							00000000		.ADDRESS	P.AAT	:
						31 50	000A4	P.AAV:	.ASCII	\P1\	:
							000A6		.BLKB	2	:
							00000002	P.AAU:	.LONG	2	:
							00000000		.ADDRESS	P.AAV	:
59	54	49	52	4F	49	52 50	000B0	P.AAX:	.ASCII	\PRIORITY\	:
							00000008	P.AAW:	.LONG	8	:
							00000000		.ADDRESS	P.AAX	:
53	45	47	45	4C	49	56 49 52 50	000C0	P.AAZ:	.ASCII	\PRIVILEGES\	:
							000CA		.BLKB	2	:
							0000000A	P.AAY:	.LONG	10	:
							00000000		.ADDRESS	P.AAZ	:
45	4D	41	4E	5F	53	53 45 43 4F 52 50	000D4	P.ABB:	.ASCII	\PROCESS_NAME\	:
							0000000C	P.ABA:	.LONG	12	:
							00000000		.ADDRESS	P.ABB	:
54	49	41	57	5F	45	43 52 55 4F 53 45 52	000E4	P.ABD:	.ASCII	\RESOURCE_WAIT\	:
							000F5		.BLKB	3	:
							0000000D	P.ABC:	.LONG	13	:
							00000000		.ADDRESS	P.ABD	:
						45 4C 55 44 45 48 43 53	00100	P.ABF:	.ASCII	\SCHEDULE\	:
							00000008	P.ABE:	.LONG	8	:
							00000000		.ADDRESS	P.ABF	:
45	52	55	4C	49	41	46 5F 45 43 49 56 52 45 53	00110	P.ABH:	.ASCII	\SERVICE_FAILURE\	:
							0011F		.BLKB	1	:
							0000000F	P.ABG:	.LONG	15	:
							00000000		.ADDRESS	P.ABH	:
						47 4E 49 50 50 41 57 53	00128	P.ABJ:	.ASCII	\SWAPPING\	:
							00000008	P.ABI:	.LONG	8	:
							00000000		.ADDRESS	P.ABJ	:
						43 49 55	00134	P.ABL:	.ASCII	\UIC\	:
							0013B		.BLKB	1	:
							00000003	P.ABK:	.LONG	3	:
							00000000		.ADDRESS	P.ABL	:
						54 49 4D 49 4C 5F 54 53 41	00144	P.ABN:	.ASCII	\AST_LIMIT\	:
							0014D		.BLKB	3	:
							00000009	P.ABM:	.LONG	9	:
							00000000		.ADDRESS	P.ABN	:
						54 49 4D 49 4C 5F 52 45 46 46 55 42	00158	P.ABP:	.ASCII	\BUFFER_LIMIT\	:
							0000000C	P.ABO:	.LONG	12	:
							00000000		.ADDRESS	P.ABP	:
54	49	4D	49	4C	5F	45 55 45 55 51 4E 45	0016C	P.ABR:	.ASCII	\ENQUEUE_LIMIT\	:
							00179		.BLKB	3	:
							0000000D	P.ABQ:	.LONG	13	:
							00000000		.ADDRESS	P.ABR	:
						54 4E 45 54 58 45	00184	P.ABT:	.ASCII	\EXTENT\	:
							0018A		.BLKB	2	:
							00000006	P.ABS:	.LONG	6	:
							00000000		.ADDRESS	P.ABT	:
						54 49 4D 49 4C 5F 45 4C 49 46	00194	P.ABV:	.ASCII	\FILE_LIMIT\	:
							0019E		.BLKB	2	:

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
run_detached -- Create a sub or detached proces

I 13

16-Sep-1984 00:27:00

14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742

[CLIUTL.SRC]RUNDET.B32;1

Page 11

(6)

```
0000000A 001A0 P.ABU: .LONG 10
00000000 001A4 .ADDRESS P.ABV
44 45 52 45 46 46 55 42 5F 4F 49 001A8 P.ABX: .ASCII \IO_BUFFERED\
001B3 .BLKB 1
0000000B 001B4 P.ABW: .LONG 11
00000000 001B8 .ADDRESS P.ABX
54 43 45 52 49 44 5F 4F 49 001BC P.ABZ: .ASCII \IO_DIRECT\
001C5 .BLKB 3
00000009 001C8 P.ABY: .LONG 9
00000000 001CC .ADDRESS P.ABZ
47 4E 49 4B 52 4F 57 5F 4D 55 4D 49 58 41 4D 001D0 P.ACB: .ASCII \MAXIMUM_WORKING_SET\
54 45 53 5F 001DF .BLKB 1
00000013 001E4 P.ACA: .LONG 19
00000000 001E8 .ADDRESS P.ACB
45 4C 49 46 5F 45 47 41 50 001EC P.ACD: .ASCII \PAGE_FILE\
001F5 .BLKB 3
00000009 001F8 P.ACC: .LONG 9
00000000 001FC .ADDRESS P.ACD
54 49 4D 49 4C 5F 45 55 45 55 51 00200 P.ACF: .ASCII \QUEUE_LIMIT\
0020B .BLKB 1
0000000B 0020C P.ACE: .LONG 11
00000000 00210 .ADDRESS P.ACF
49 4D 49 4C 5F 53 53 45 43 4F 52 50 42 55 53 00214 P.ACH: .ASCII \SUBPROCESS_LIMIT\
54 00223 .BLKB 2
00000010 00224 P.ACG: .LONG 16
00000000 00228 .ADDRESS P.ACH
54 49 4D 49 4C 5F 45 4D 49 54 0022C P.ACJ: .ASCII \TIME_LIMIT\
00236 .BLKB 2
0000000A 00238 P.ACI: .LONG 10
00000000 0023C .ADDRESS P.ACJ
54 45 53 5F 47 4E 49 4B 52 4F 57 00240 P.ACL: .ASCII \WORKING_SET\
0024B .BLKB 1
0000000B 0024C P.ACK: .LONG 11
00000000 00250 .ADDRESS P.ACL
41 54 4F 55 51 5F 45 4C 42 41 54 5F 42 4F 4A 00254 P.ACN: .ASCII \JOB_TABLE_QUOTA\
00263 .BLKB 1
0000000F 00264 P.ACM: .LONG 15
00000000 00268 .ADDRESS P.ACN
```

.PSECT \$OWNS,NOEXE,2

```
00000 RUNSA_ERROR:
      .BLKB 8
00008 RUNSA_IMAGE:
      .BLKB 8
00010 RUNSA_INPUT:
      .BLKB 8
00018 RUNSA_INPUT_DESC:
      .BLKB 8
00020 RUNSA_OUTPUT:
      .BLKB 8
00028 RUNSA_PRCNAM:
      .BLKB 8
00030 RUNSA_QUOTA:
      .BLKB 4
00034 RUNSL_BASPRI:
```

```

                                .BLKB 4
00038 RUNSL_MBXUNT:
                                .BLKB 4
0003C RUNSL_PID:
                                .BLKB 4
00040 RUNSL_STATUS:
                                .BLKB 4
00044 RUNSL_STSFLG:
                                .BLKB 4
00048 RUNSL_UIC:
                                .BLKB 4
FFFFFFFF FFFFFFFF 0004C RUNSQ_DAYTIM:
                                .LONG -1, -1
00000000 00000000 00054 RUNSQ_INTERVAL:
                                .LONG 0, 0
0005C RUNSQ_PRVADR:
                                .BLKB 8
00064 RUNSA_IMAGE_BUF:
                                .BLKB 255
00163 .BLKB 1
00164 RUNSA_FINDFILE:
                                .BLKB 4
0309 0004 00168 RUNSA_GETJPI:
                                .WORD 4, 777
00000000' 0016C .ADDRESS RUNSL_BASPRI
00000000 00170 .LONG 0
0204 0008 00174 .WORD 8, 516
00000000' 00178 .ADDRESS RUNSQ_PRVADR
00000000 0017C .LONG 0
0000 0000 00180 .WORD 0, 0
00000000 00184 .LONG 0, 0
01 0018C RUNSA_QUOTA_TBL:
                                .BYTE 1
00000000' 0018D .ADDRESS P.ABM
03 00191 .BYTE 3
00000000' 00192 .ADDRESS P.ABO
0C 00196 .BYTE 12
00000000' 00197 .ADDRESS P.ABQ
0D 0019B .BYTE 13
00000000' 0019C .ADDRESS P.ABS
06 001A0 .BYTE 6
00000000' 001A1 .ADDRESS P.ABU
02 001A5 .BYTE 2
00000000' 001A6 .ADDRESS P.ABW
05 001AA .BYTE 5
00000000' 001AB .ADDRESS P.ABY
0A 001AF .BYTE 10
00000000' 001B0 .ADDRESS P.ACA
07 001B4 .BYTE 7
00000000' 001B5 .ADDRESS P.ACC
09 001B9 .BYTE 9
00000000' 001BA .ADDRESS P.ACE
08 001BE .BYTE 8
00000000' 001BF .ADDRESS P.ACG
04 001C3 .BYTE 4
00000000' 001C4 .ADDRESS P.ACI
0B 001C8 .BYTE 11

```


00000000' 001C9 .ADDRESS P.ACK
OE 001CD .BYTE 14
00000000' 001CE .ADDRESS P.ACM

RUNS_INSVIRMEM== 12587764
RUNS_INVQUAVAL== 12587818
RUNS_PARSEFAIL== 12587596
RUNS_SYNTAX== 12587260
ACCOUNTING= P.AAA
AUTHORIZE= P.AAC
DELAY= P.AAE
DETACH= P.AAG
DUMP= P.AAI
ERROR= P.AAK
INPUT= P.AAM
INTERVAL= P.AAO
MAILBOX= P.AAQ
OUTPUT= P.AAS
P1= P.AAU
PRIORITY= P.AAW
PRIVILEGES= P.AAY
PROCESS= P.ABA
RESOURCE_WAIT= P.ABC
SCHEDULE= P.ABE
SERVICE_FAIL= P.ABG
SWAPPING= P.ABI
UIC= P.ABK
.EXTRN CLISGET_VALUE, CLISPRESENT
.EXTRN LIBSCVT_DTIME, LIBSCVT_DX_DX
.EXTRN LIBSCVT_TIME, LIBSGET_VM
.EXTRN LIBSFIND_FILE, LIBSTPARSE
.EXTRN PRVSSETPRIV, CLIS_NEGATED
.EXTRN RUNS_CREPRC, RUNS_PROC_ID
.EXTRN RUNS_GETJPI, RUNS_CVTERR
.EXTRN RUNS_INVUIC, RUNS_ILLVAL
.EXTRN RUNS_SCHDWK, SYSSCREPRC

.PSECT \$CODE\$,NOWRT,2

0004 00000 RUN_DETACHED:
0000V 52 0000' CF 9E 00002 .WORD Save R2
CF 00 FB 00007 MOVAB RUNSL_STSFLG, R2
7E D4 0000C CALLS #0, INIT_ARG_LIST
62 DD 0000E CLRL -(SP)
F4 A2 DD 00010 PUSHL RUNSL_STSFLG
04 A2 DD 00013 PUSHL RUNSL_MBXUNT
F0 A2 DD 00016 PUSHL RUNSL_UIC
E4 A2 9F 00019 PUSHL RUNSL_BASPRI
EC A2 DD 0001C PUSHAB RUNSA_PRCNAM
18 A2 9F 0001F PUSHL RUNSA_QUOTA
BC A2 9F 00022 PUSHAB RUNSQ_PRIVADR
DC A2 9F 00025 PUSHAB RUNSA_ERROR
CC A2 9F 00028 PUSHAB RUNSA_OUTPUT
C4 A2 9F 0002B PUSHAB RUNSA_INPUT
F8 A2 9F 0002E PUSHAB RUNSA_IMAGE
00000000G 00 OD FB 00031 CALLS RUNSL_PID
CALLS #13, SYSSCREPRC

0249
0282
0295

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
run_detached -- Create a sub or detached proces

L 13
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 14
(6)

FC	A2	50	D0	00038	MOVL	R0, RUNSL_STATUS	
	14	50	E8	0003C	BLBS	R0, 1\$	
		FC	A2	DD 0003F	PUSHL	RUNSL_STATUS	0297
			7E	D4 00042	CLRL	-(SP)	
00000000G	00		8F	DD 00044	PUSHL	#RUN\$ CREPRC	
			03	FB 0004A	CALLS	#3, LIB\$STOP	
			12	11 00051	BRB	2\$	
		F8	A2	DD 00053 1\$:	PUSHL	RUNSL_PID	0299
			01	DD 00056	PUSHL	#1	
00000000G	00		8F	DD 00058	PUSHL	#RUN\$ PROC_ID	
05	62		03	FB 0005E	CALLS	#3, LIB\$SIGNAL	0301
0000V	CF		05	E1 00065 2\$:	BBC	#5, RUNSL_STSFLG, 3\$	0302
			00	FB 00069	CALLS	#0, SCHEDULE_PROCESS	0304
			04	0006E 3\$:	RET		

; Routine Size: 111 bytes, Routine Base: \$CODE\$ + 0000

; 310 0305 1


```

312 0306 1 %SBTTL 'init_arg_list -- Initialize argument lists'
313 0307 1 ROUTINE init_arg_list : NOVALUE =
314 0308 1 ++
315 0309 1
316 0310 1 Functional Description:
317 0311 1
318 0312 1 This routine is responsible for calling the procedures to parse
319 0313 1 the command line and establish the arguments for creating and
320 0314 1 scheduling the requested process.
321 0315 1
322 0316 1 Implicit Inputs:
323 0317 1
324 0318 1 Global data for the argument lists, command line entities etc..
325 0319 1
326 0320 1 Implicit Outputs:
327 0321 1
328 0322 1 The command line has been parsed with the resultant information
329 0323 1 available for calls to the create process ($CREPRC) and the schedule
330 0324 1 wake up ($SCHDWK) system services.
331 0325 1
332 0326 1 Side Effects:
333 0327 1
334 0328 1 Errors encountered during initialization will be signalled by
335 0329 1 the routine which detected the problem.
336 0330 1
337 0331 1 --
338 0332 2 BEGIN
339 0333 2
340 0334 2 Initialize the various descriptors.
341 0335 2
342 0336 2 CH$FILL (0, dsc$c_s_bln, run$a_image);      ! Image file specification descriptor.
343 0337 2 CH$FILL (0, dsc$c_s_bln, run$a_input);      ! Input device specification descriptor.
344 0338 2 CH$FILL (0, dsc$c_s_bln, run$a_input_desc);  ! Initialize the dynamic input descriptor.
345 0339 2 CH$FILL (0, dsc$c_s_bln, run$a_output);      ! Output device specification descriptor.
346 0340 2 CH$FILL (0, dsc$c_s_bln, run$a_error);      ! Error device specification descriptor.
347 0341 2 CH$FILL (0, dsc$c_s_bln, run$a_prcnam);      ! Process name descriptor.
348 0342 2 run$a_input [dsc$b_class] = dsc$k_class_d;  ! Input device.
349 0343 2 run$a_output [dsc$b_class] = dsc$k_class_d;  ! Output device.
350 0344 2 run$a_error [dsc$b_class] = dsc$k_class_d;   ! Error device.
351 0345 2 run$a_prcnam [dsc$b_class] = dsc$k_class_d;  ! Process name.
352 0346 2 run$a_input_desc [dsc$b_dtype] = dsc$k_dtype_t; ! General purpose input descriptor (type req for con
353 0347 2 run$a_input_desc [dsc$b_class] = dsc$k_class_d; ! General purpose input descriptor.
354 0348 2
355 0349 2 IF NOT (run$l_status = $GETJPI (ITMLST = run$a_getjpi)) ! Obtain the necessary job and process info.
356 0350 2 THEN SIGNAL_STOP (run$_getjpi, 0, .run$l_status); ! If we encounter an error, quit.
357 0351 2
358 0352 2 CLISGET_VALUE (input, run$a_input);          ! Obtain the input device specification.
359 0353 2 CLISGET_VALUE (output, run$a_output);        ! Obtain the output device specification.
360 0354 2 CLISGET_VALUE (error, run$a_error);          ! Obtain the error device specification.
361 0355 2 CLISGET_VALUE (process, run$a_prcnam);       ! Obtain the process name.
362 0356 2
363 0357 2 parse_image_spec ();                        ! Obtain the expanded image file specification.
364 0358 2 get_value (mailbox, run$l_mbxunt);          ! Get the mailbox unit number if supplied.
365 0359 2 get_value (priority, run$l_baspri);         ! Get the process base priority if supplied.
366 0360 2 get_wakeup_info ();                        ! See if we should leave a wake up call.
367 0361 2 get_uic ();                               ! Get the user identification code (UIC).
368 0362 2 get_privileges ();                         ! Set up the process privilege vector.

```

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
init_arg_list -- Initialize argument lists

N 13
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 16
(7)

: 369
: 370
: 371
: 372

0363 2 get_quotas ();
0364 2 get_stsflgs ();
0365 2
0366 1 END; ! of ROUTINE init_arg_list

! Set up the default process quotas.
! Set up the initial process context flags.

```
.EXTRN SYSSGETJPI

01FC 00000 INIT_ARG_LIST:
      58 0000' CF 9E 00002      WORD      Save R2,R3,R4,R5,R6,R7,R8      : 0307
      57 00000000G 00 9E 00007      MOVAB     INPUT, R8
      56 0000' CF 9E 0000E      MOVAB     CLISGET VALUE, R7
      6E      F8 00 2C 00013      MOVAB     RUNSA_INPUT, R6
      6E      F8 00 2C 00018      MOVCS     #0, (SP), #0, #8, RUNSA_IMAGE      : 0336
      6E      66 00 2C 0001A      MOVCS     #0, (SP), #0, #8, RUNSA_INPUT      : 0337
      6E      66 00 2C 0001F      MOVCS     #0, (SP), #0, #8, RUNSA_INPUT_DESC      : 0338
      6E      08 00 2C 00025      MOVCS     #0, (SP), #0, #8, RUNSA_OUTPUT      : 0339
      6E      10 00 2C 00027      MOVCS     #0, (SP), #0, #8, RUNSA_ERROR      : 0340
      6E      F0 00 2C 0002E      MOVCS     #0, (SP), #0, #8, RUNSA_PRCNAM      : 0341
      6E      18 00 2C 00035      MOVCS     #0, (SP), #0, #8, RUNSA_PRCNAM
      03 A6      02 90 0003A      MOVAB     #2, RUNSA_INPUT+3      : 0342
      13 A6      02 90 0003C      MOVAB     #2, RUNSA_OUTPUT+3      : 0343
      F3 A6      02 90 00040      MOVAB     #2, RUNSA_ERROR+3      : 0344
      1B A6      02 90 00044      MOVAB     #2, RUNSA_PRCNAM+3      : 0345
      0A A6      02 90 00048      MOVW      #526, RUNSA_INPUT_DESC+2      : 0346
      020E 8F B0 0004C      CLRQ      -(SP)
      7E 7C 00052      CLRL      -(SP)
      0158 7E D4 00054      PUSHAB     RUNSA_GETJPI
      7E 7C 00056      CLRQ      -(SP)
      7E D4 0005A      CLRL      -(SP)
      00000000G 00 07 FB 0005C      CALLS     #7, SYSSGETJPI
      30 A6      50 D0 0005E      MOVL      R0, RUNSL_STATUS
      12      50 E8 00065      BLBS      R0, 1$
      30 A6 DD 00069      PUSHL     RUNSL_STATUS      : 0350
      7E D4 0006C      CLRL      -(SP)
      00000000G 00 8F DD 0006F      PUSHL     #RUNS_GETJPI
      00000000G 00 03 FB 00071      CALLS     #3, LIB$STOP
      56 DD 00077      PUSHL     R6      : 0352
      58 DD 00080      PUSHL     R8
      67 02 FB 00082      CALLS     #2, CLISGET VALUE
      10 A6 9F 00085      PUSHAB     RUNSA_OUTPUT      : 0353
      30 A8 9F 00088      PUSHAB     OUTPUT
      67 02 FB 0008B      CALLS     #2, CLISGET VALUE
      F0 A6 9F 0008E      PUSHAB     RUNSA_ERROR
      F0 A8 9F 00091      PUSHAB     ERROR      : 0354
      67 02 FB 00094      CALLS     #2, CLISGET VALUE
      18 A6 9F 00097      PUSHAB     RUNSA_PRCNAM      : 0355
      74 A8 9F 0009A      PUSHAB     PROCESS
      0000V 67 02 FB 0009D      CALLS     #2, CLISGET VALUE
      CF      00 FB 000A0      CALLS     #0, PARSE_IMAGE_SPEC
      28 A6 9F 000A5      PUSHAB     RUNSL_MBXUNT      : 0357
      : 0358
```


RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
init_arg_list -- Initialize argument lists

B 14
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 17
(7)

0000V	CF	20	A8	9F	000A8
			02	FB	000AB
		24	A6	9F	000B0
		4C	A8	9F	000B3
0000V	CF		02	FB	000B6
0000V	CF		00	FB	000BB
0000V	CF		00	FB	000C0
0000V	CF		00	FB	000C5
0000V	CF		00	FB	000CA
0000V	CF		00	FB	000CF
			04	000D4	

PUSHAB	MAILBOX
CALLS	#2, GET_VALUE
PUSHAB	RUNSL_BASPRI
PUSHAB	PRIORITY
CALLS	#2, GET_VALUE
CALLS	#0, GET_WAKEUP_INFO
CALLS	#0, GET_UIC
CALLS	#0, GET_PRIVILEGES
CALLS	#0, GET_QUOTAS
CALLS	#0, GET_STSFLGS
RET	

:
:
: 0359
:
:
: 0360
: 0361
: 0362
: 0363
: 0364
: 0366

; Routine Size: 213 bytes, Routine Base: \$CODE\$ + 006F

; 373 0367 1


```
375 0368 1 %SBTTL 'parse_image_spec -- Parse image file specification'
376 0369 1 ROUTINE parse_image_spec : NOVALUE =
377 0370 1 ++
378 0371 1
379 0372 1 Functional Description:
380 0373 1
381 0374 1 This routine obtains the image file specification from the command
382 0375 1 line and parses it, producing a resultant file specification with
383 0376 1 defaults applied.
384 0377 1
385 0378 1 Implicit Inputs:
386 0379 1
387 0380 1 none
388 0381 1
389 0382 1 Implicit Outputs:
390 0383 1
391 0384 1 The image file has been parsed with the resultant file specification in
392 0385 1 run$a_image_buf, and the appropriate fields of the descriptor run$a_image
393 0386 1 initialized.
394 0387 1
395 0388 1 Side Effects:
396 0389 1
397 0390 1 Parse errors from RMS or errors from LIB$FIND_FILE will result
398 0391 1 with a FATAL error signalled.
399 0392 1
400 0393 1 --
401 0394 2 BEGIN
402 0395 2
403 0396 2 bind
404 0397 2 default_name = uplit (%charcount('.EXE'),uplit byte ('.EXE'));
405 0398 2
406 0399 2 local
407 0400 2 status,
408 0401 2 findfilenam : ref block [ ,byte ];
409 0402 2
410 0403 2 CLISGET_VALUE (p1, run$a_input_desc); ! Obtain the image file specification.
411 0404 2
412 0405 2 run$a_image [DSC$B_CLASS] = DSC$K_CLASS_D;
413 0406 2 run$a_image [DSC$B_DTYPE] = DSC$K_DTYPE_T;
414 0407 2
415 0408 2 ! Get the next file name to search for, no wildcards permitted.
416 0409 2
417 0410 2 status = LIB$FIND_FILE(
418 0411 2 run$a_input_desc, run$a_image,
419 0412 2 run$a_findfile,
420 0413 2 default_name, 0, 0, %REF(1));
421 0414 2
422 0415 2 ! If the filename has wildcards in it it's an error
423 0416 2
424 0417 2 if (.status and sts$m_msg_no) eql shr$_nowild
425 0418 2 then
426 0419 2 run$a_findfile [fab$l_sts] = .status;
427 0420 2
428 0421 2 ! Report miscellaneous errors from LIB$FIND_FILE
429 0422 2
430 0423 2 if not .status
431 0424 2 then
```



```

: 432 0425 2 SIGNAL_STOP (run$parsefail, 1,
: 433 0426 2 run$a_input_desc, .run$a_findfile [fab$l_sts], .run$a_findfile [fab$l_stv]);
: 434 0427 2
: 435 0428 2 findfilenam = .run$a_findfile [fab$l_nam];
: 436 0429 2
: 437 0430 2 ! If an explicit version number was not specified, remove the version number.
: 438 0431 2
: 439 0432 2 IF NOT .findfilenam [nam$b_exp_ver]
: 440 0433 2 THEN
: 441 0434 2 run$a_image [dsc$b_length] = .run$a_image [dsc$b_length] - .findfilenam [nam$b_ver];
: 442 0435 2
: 443 0436 1 END; ! of ROUTINE parse_image_spec
```

.PSECT SPLITS,NOWRT,NOEXE,2

```

45 58 45 2E 0026C P.ACP: .ASCII \.EXE\
00000004 00270 P.ACO: .LONG 4
00000000' 00274 .ADDRESS P.ACP
```

DEFAULT_NAME= P.ACO

.PSECT \$CODE\$,NOWRT,2

0004 00000 PARSE_IMAGE SPEC:

	52	0000'	CF	9E	00002	.WORD	Save R2	0369
	5E		04	C2	00007	MOVAB	RUN\$a_FINDFILE, R2	
		FEB4	C2	9F	0000A	SUBL2	#4, SP	0403
		0000'	CF	9F	0000E	PUSHAB	RUN\$a_INPUT_DESC	
00000000G	00		02	FB	00012	PUSHAB	P1	
FEA6	C2	020E	8F	B0	00019	CALLS	#2, CLISGET_VALUE	0406
	6E		01	D0	00020	MOVW	#526, RUN\$a_IMAGE+2	0413
			5E	DD	00023	MOVL	#1, (SP)	
			7E	7C	00025	PUSHL	SP	
		0000'	CF	9F	00027	CLRQ	-(SP)	0410
			52	DD	0002B	PUSHAB	DEFAULT_NAME	
		FEA4	C2	9F	0002D	PUSHL	R2	
		FEB4	C2	9F	00031	PUSHAB	RUN\$a_IMAGE	
00000000G	00		07	FB	00035	PUSHAB	RUN\$a_INPUT_DESC	
	51		50	D0	0003C	CALLS	#7, LIB\$FIND_FILE	
50	51	FFFF0007	8F	CB	0003F	MOVL	R0, STATUS	0417
00001128	8F		50	D1	00047	BICL3	#-65529, STATUS, R0	
			07	12	0004E	CMPL	R0, #4392	
	50		62	D0	00050	BNEQ	1\$	
	A0		51	D0	00053	MOVL	RUN\$a_FINDFILE, R0	0419
08	1A		51	E8	00057	MOVL	STATUS, 8(R0)	0423
	50		62	D0	0005A	BLBS	STATUS, 2\$	0426
	7E	08	A0	7D	0005D	MOVL	RUN\$a_FINDFILE, R0	
		FEB4	C2	9F	00061	MOVQ	8(R0), -(SP)	0425
			01	DD	00065	PUSHAB	RUN\$a_INPUT_DESC	
		00C0124C	8F	DD	00067	PUSHL	#1	
00000000G	00		05	FB	0006D	PUSHL	#12587596	
	50		62	D0	00074	CALLS	#5, LIB\$STOP	0428
	50	28	A0	D0	00077	MOVL	RUN\$a_FINDFILE, R0	
						MOVL	40(R0), FINDFILNAM	

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure E 14
parse_image_spec -- Parse image file specificat 16-Sep-1984 00:27:00 VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1
14-Sep-1984 12:08:54

Page 20
(8)

	09	34	A0	E8	0007B	BLBS	52(FINDFILENAM), 3\$	
	51	3D	A0	9A	0007F	MOVZBL	61(FINDFILENAM), R1	
FEA4	C2		51	A2	00083	SUBW2	R1, RUNSA_IMAGE	
			04	00088	3\$:	RET		

: 0432
: 0434
: 0436

; Routine Size: 137 bytes, Routine Base: \$CODE\$ + 0144

: 444 0437 1


```

446 0438 1 %SBTTL 'get_wakeup_info -- Process the $$CHDWK time values'
447 0439 1 ROUTINE get_wakeup_info : NOVALUE =
448 0440 1 ++
449 0441 1
450 0442 1 Functional Description:
451 0443 1
452 0444 1 This routine is responsible for obtaining and converting the time values
453 0445 1 used to schedule wake up requests for the created process.
454 0446 1
455 0447 1 Implicit Outputs:
456 0448 1
457 0449 1 run$q_interval      delta      Reschedule the process to execute at
458 0450 1                                     this interval.
459 0451 1
460 0452 1 run$q_daytim        absolute or  Schedule the process to execute at
461 0453 1                        delta      this time.
462 0454 1
463 0455 1 Side Effects:
464 0456 1
465 0457 1 The time quantities are obtained as .ASCII strings from the CLI. To
466 0458 1 convert them we call the appropriate library routine. Any errors
467 0459 1 encountered during the conversion will be signalled, and execution
468 0460 1 of this image terminated.
469 0461 1
470 0462 1 --
471 0463 2 BEGIN
472 0464 2
473 0465 2 IF CLISGET_VALUE (delay, run$a_input_desc)      ! Was /DELAY specified?
474 0466 2 THEN
475 0467 3 IF NOT (run$l_status = LIB$CVT_DTIME (run$a_input_desc, run$q_daytim))
476 0468 2 THEN
477 0469 2 SIGNAL_STOP (run$cvterr, 2, delay, run$a_input_desc, .run$l_status);
478 0470 2
479 0471 2 IF CLISGET_VALUE (interval, run$a_input_desc) ! Was /INTERVAL specified?
480 0472 2 THEN
481 0473 3 IF NOT (run$l_status = LIB$CVT_DTIME (run$a_input_desc, run$q_interval))
482 0474 2 THEN
483 0475 2 SIGNAL_STOP (run$cvterr, 2, interval, run$a_input_desc, .run$l_status);
484 0476 2
485 0477 2 IF CLISGET_VALUE (schedule, run$a_input_desc) ! How about /SCHEDULE?
486 0478 2 THEN
487 0479 3 IF NOT (run$l_status = LIB$CVT_TIME (run$a_input_desc, run$q_daytim))
488 0480 2 THEN
489 0481 2 SIGNAL_STOP (run$cvterr, 2, schedule, run$a_input_desc, .run$l_status);
490 0482 2
491 0483 1 END;      ! of ROUTINE get_wakeup_info

```

00FC 00000 GET_WAKEUP INFO:

57	00000000G	00	9E	00002	.WORD	Save R2,R3,R4,R5,R6,R7
56	00000000G	00	9E	00009	MOVAB	LIB\$CVT_DTIME, R7
55	00000000G	8F	D0	00010	MOVAB	LIB\$STOP, R6
54	00000000G	00	9E	00017	MOVL	#RUN\$ CVTERR, R5
					MOVAB	CLISGET_VALUE, R4

0439

53	0000'	CF	9E	0001E	MOVAB	DELAY, R3		
52	0000'	CF	9E	00023	MOVAB	RUNSA_INPUT_DESC, R2		
		52	DD	00028	PUSHL	R2	0465	
		53	DD	0002A	PUSHL	R3		
64		02	FB	0002C	CALLS	#2, CLISGET_VALUE		
1D		50	E9	0002F	BLBC	R0, 1\$		
	34	A2	9F	00032	PUSHAB	RUNSQ_DAYTIM	0467	
		52	DD	00035	PUSHL	R2		
67		02	FB	00037	CALLS	#2, LIBSCVT_DTIME		
28	A2	50	DD	0003A	MOVL	R0, RUNSL_STATUS		
	0E	50	E8	0003E	BLBS	R0, 1\$		
		28	A2	DD	00041	PUSHL	RUNSL_STATUS	0469
			52	DD	00044	PUSHL	R2	
			53	DD	00046	PUSHL	R3	
			02	DD	00048	PUSHL	#2	
			55	DD	0004A	PUSHL	R5	
66		05	FB	0004C	CALLS	#5, LIB\$STOP		
		52	DD	0004F	PUSHL	R2	0471	
	4C	A3	9F	00051	PUSHAB	INTERVAL		
64		02	FB	00054	CALLS	#2, CLISGET_VALUE		
1E		50	E9	00057	BLBC	R0, 2\$		
	3C	A2	9F	0005A	PUSHAB	RUNSQ_INTERVAL	0473	
		52	DD	0005D	PUSHL	R2		
67		02	FB	0005F	CALLS	#2, LIBSCVT_DTIME		
28	A2	50	DD	00062	MOVL	R0, RUNSL_STATUS		
	0F	50	E8	00066	BLBS	R0, 2\$		
		28	A2	DD	00069	PUSHL	RUNSL_STATUS	0475
			52	DD	0006C	PUSHL	R2	
	4C	A3	9F	0006E	PUSHAB	INTERVAL		
		02	DD	00071	PUSHL	#2		
		55	DD	00073	PUSHL	R5		
66		05	FB	00075	CALLS	#5, LIB\$STOP		
		52	DD	00078	PUSHL	R2	0477	
	00D8	C3	9F	0007A	PUSHAB	SCHEDULE		
64		02	FB	0007E	CALLS	#2, CLISGET_VALUE		
23		50	E9	00081	BLBC	R0, 3\$		
	34	A2	9F	00084	PUSHAB	RUNSQ_DAYTIM	0479	
		52	DD	00087	PUSHL	R2		
00000000G	00	02	FB	00089	CALLS	#2, LIBSCVT_TIME		
28	A2	50	DD	00090	MOVL	R0, RUNSL_STATUS		
	10	50	E8	00094	BLBS	R0, 3\$		
		28	A2	DD	00097	PUSHL	RUNSL_STATUS	0481
			52	DD	0009A	PUSHL	R2	
	00D8	C3	9F	0009C	PUSHAB	SCHEDULE		
		02	DD	000A0	PUSHL	#2		
		55	DD	000A2	PUSHL	R5		
66		05	FB	000A4	CALLS	#5, LIB\$STOP		
		04	000A7	3\$:	RET		0483	

; Routine Size: 168 bytes, Routine Base: \$CODE\$ + 01CD

; 492 0484 1


```

494 0485 1 %SBTTL 'get_uic -- Process the UIC, converting it to a longword value'
495 0486 1 ROUTINE get_uic : NOVALUE =
496 0487 1 ++
497 0488 1
498 0489 1 Functional Description:
499 0490 1
500 0491 1 This routine is responsible for obtaining and converting a UIC string
501 0492 1 of the form [group, member] to a longword value.
502 0493 1
503 0494 1 Implicit Inputs:
504 0495 1
505 0496 1 run$a_input_desc adr Address of a general purpose dynamic
506 0497 1 string descriptor.
507 0498 1
508 0499 1 Side Effects:
509 0500 1
510 0501 1 If the UIC could not be converted, we will inform the user with
511 0502 1 an invalid UIC diagnostic and exit.
512 0503 1
513 0504 1 --
514 0505 2 BEGIN
515 0506 2
516 0507 2 LOCAL
517 0508 2 TPA_PARAM : $BBLOCK [TPA$K_LENGTH0]
518 0509 2 INITIAL (REP TPA$K_LENGTH0 OF BYTE (0));
519 0510 2
520 0511 2 IF CLISGET_VALUE (uic, run$a_input_desc) ! If the user supplied a UIC
521 0512 2 THEN ! convert it to a longword value.
522 0513 2 BEGIN
523 0514 2 tpa_param [tpa$l_count] = tpa$k_count0;
524 0515 2 tpa_param [tpa$l_stringcnt] = .run$a_input_desc [dsc$w_length];
525 0516 2 tpa_param [tpa$l_stringptr] = .run$a_input_desc [dsc$a_pointer];
526 0517 2
527 0518 2 IF NOT LIB$TPARSE (tpa_param, uic_states, uic_keys)
528 0519 2 THEN
529 0520 2 SIGNAL_STOP (run$_invaic, 1, run$a_input_desc); ! converting the UIC, inform the user.
530 0521 2 END;
531 0522 2
532 0523 1 END; ! of ROUTINE get_uic

```

.PSECT \$PLITS\$,NOWRT,NOEXE,2

00# 00278 P.ACQ: .BYTE 0[36]

.PSECT \$CODE\$,NOWRT,2

			007C 00000	GET_UIC:	WORD	Save R2,R3,R4,R5,R6	
		56	0000'	CF	9E 00002	MOVAB	RUN\$a_INPUT_DESC, R6
		5E		24	C2 00007	SUBL2	#36, SP
6E	0000'	CF		24	28 0000A	MOVCS	#36, P.ACQ, TPA_PARAM
				56	DD 00010	PUSHL	R6
			0000'	CF	9F 00012	PUSHAB	UIC
	00000000G	00		02	FB 00016	CALLS	#2, CLISGET_VALUE

0486
0509
0511

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_uic -- Process the UIC, converting it to a

I 14
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 24
(10)

	32		50	E9	0001D	BLBC	R0, 1\$		
	6E		08	D0	00020	MOVL	#8, TPA_PARAM	:	0514
08	AE		66	3C	00023	MOVZWL	RUNSA_INPUT_DESC, TPA_PARAM+8	:	0515
0C	AE	04	A6	D0	00027	MOVL	RUNSA_INPUT_DESC+4, TPA_PARAM+12	:	0516
		0000'	CF	9F	0002C	PUSHAB	UIC_KEYS	:	0518
		0000'	CF	9F	00030	PUSHAB	UIC_STATES	:	
		08	AE	9F	00034	PUSHAB	TPA_PARAM	:	
00000000G	00		03	FB	00037	CALLS	#3, LIB\$TPARSE	:	
	11		50	E8	0003E	BLBS	R0, 1\$:	0520
			56	DD	00041	PUSHL	R6	:	
			01	DD	00043	PUSHL	#1	:	
		00000000G	8F	DD	00045	PUSHL	#RUN\$ INVUIC	:	
00000000G	00		03	FB	0004B	CALLS	#3, LIB\$STOP	:	0523
			04	00052	1\$:	RET		:	

; Routine Size: 83 bytes, Routine Base: \$CODE\$ + 0275

; 533 0524 1


```

535 0525 1 %SBTTL 'get_privileges -- Obtain the process privileges'
536 0526 1 ROUTINE get_privileges : NOVALUE =
537 0527 1 ++
538 0528 1
539 0529 1 Functional Description:
540 0530 1
541 0531 1 This routine iteratively calls the routine CLISGET_VALUE to obtain the
542 0532 1 privileges specified by the user. The private CLI routine PRV$SETPRIV
543 0533 1 is then called to convert the ascii string name into a bit number and
544 0534 1 set/clear the appropriate bit in the privilege mask.
545 0535 1
546 0536 1 Implicit Inputs:
547 0537 1
548 0538 1 prv$a_input_desc adr Address of a general purpose dynamic
549 0539 1 string descriptor.
550 0540 1 prv$q_privadr adr Address of the privilege mask quadword.
551 0541 1
552 0542 1 Implicit Outputs:
553 0543 1
554 0544 1 The privilege vector has been established. The privileges are set/cleared
555 0545 1 according to whether they were explicitly specified, explicitly negated
556 0546 1 or set as a result of the 'SAME' privilege.
557 0547 1
558 0548 1 Side Effects:
559 0549 1
560 0550 1 The 'SAME' privilege is special cased...
561 0551 1
562 0552 1 If an invalid privilege keyword is detected we will signal a fatal error.
563 0553 1
564 0554 1 --
565 0555 2 BEGIN
566 0556 2
567 0557 2 BIND
568 0558 2 same = $descriptor ('SAME'): $bblock,
569 0559 2 nosame = $descriptor ('NOSAME'): $bblock;
570 0560 2
571 0561 3 IF (CLISPRESENT ($descriptor ('PRIVILEGES.SAME'))) EQL cli$_negated) ! Default action is to use t
572 0562 2 THEN run$q_privadr [1] = run$q_privadr [0] = 0; ! privileges as the creating
573 0563 2
574 0564 2 WHILE CLISGET_VALUE (privileges, run$a_input_desc) ! Preclude an invalid keyword
575 0565 2 DO ! screening out the '[NO]SAM
576 0566 2 IF CH$NEQ (.run$a_input_desc [dsc$w_length], .run$a_input_desc [dsc$a_pointer], .same [dsc$w_length], .s
577 0567 2 AND CH$NEQ (.run$a_input_desc [dsc$w_length], .run$a_input_desc [dsc$a_pointer], .nosame [dsc$w_length],
578 0568 2 THEN
579 0569 2 IF NOT prv$setpriv (run$a_input_desc, run$q_privadr)
580 0570 2 THEN SIGNAL_STOP (run$_invquaval, 2, run$a_input_desc, privileges);
581 0571 2
582 0572 1 END; ! of ROUTINE get_privileges

```

.PSECT \$SPLITS,NOWRT,NOEXE,2

```

45 4D 41 53 0029C P.ACS: .ASCII \SAME\
00000004 002A0 P.ACR: .LONG 4
00000000 002A4 .ADDRESS P.ACS
45 4D 41 53 4F 4E 002A8 P.ACU: .ASCII \NOSAME\

```

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_privileges -- Obtain the process privileges

K 14

16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 26
(11)

```

                                002AE
                                00000006 002B0 P.ACT: .BLKB 2
                                00000000' 002B4 .LONG 6
45 4D 41 53 2E 53 45 47 45 4C 49 56 49 52 50 002B8 P.ACW: .ADDRESS P.ACU
                                002C7 P.ACW: .ASCII \PRIVILEGES.SAME\
                                0000000F 002C8 P.ACV: .BLKB 1
                                00000000' 002CC P.ACV: .LONG 15
                                .ADDRESS P.ACW
                                P.ACR
                                NOSAME= P.ACT

                                .PSECT $CODE$,NOWRT,2

                                001C 00000 GET_PRIVILEGES:
                                .WORD Save R2,R3,R4
                                MOVAB RUN$A_INPUT_DESC, R4
                                PUSHAB P.ACV
                                CALLS #1, CLIS$PRESENT
                                CMPL R0, #CLIS$_NEGATED
                                BNEQ 1$
                                CLRQ RUN$Q_PRIVADR
                                44 A4 7C 0001B 1$: PUSHL R4
                                54 DD 0001E 0000' CF 9F 00020 PUSHAB PRIVILEGES
                                00000000G 00 02 FB 00024 CALLS #2, CLIS$GET_VALUE
                                00000000G 8F 50 E9 0002B BLBC R0, 2$
                                0000' CF 04 B4 64 2D 0002E CMPCS RUN$A_INPUT_DESC, @RUN$A_INPUT_DESC+4, #0, -
                                0000' DF 00036 SAME, @SAME+4
                                0000' E3 13 00039 BEQL 1$
                                0000' 64 2D 0003B CMPCS RUN$A_INPUT_DESC, @RUN$A_INPUT_DESC+4, #0, -
                                0000' DF 00043 NOSAME, @NOSAME+4
                                44 A4 9F 00048 BEQL 1$
                                54 DD 0004B PUSHAB RUN$Q_PRIVADR
                                00000000G 00 02 FB 0004D PUSHL R4
                                C7 50 E8 00054 CALLS #2, PRV$SETPRIV
                                0000' CF 9F 00057 BLBS R0, 1$
                                54 DD 0005B PUSHAB PRIVILEGES
                                02 DD 0005D PUSHL R4
                                00C0132A 8F DD 0005F PUSHL #2
                                00000000G 00 04 FB 00065 PUSHL #1258781$
                                B0 11 0006C CALLS #4, LIB$STOP
                                04 0006E 2$: BRB 1$
                                RET

```

; Routine Size: 111 bytes, Routine Base: \$CODE\$ + 02C8

; 583 0573 1


```

585 0574 1 %SBTTL 'get_quotas -- Obtain the process quota values'
586 0575 1 ROUTINE get_quotas : NOVALUE =
587 0576 1 ++
588 0577 1
589 0578 1 Functional Description:
590 0579 1
591 0580 1 This routine is responsible for establishing the quota list.
592 0581 1
593 0582 1 NOTE: The ending address of the quota table computation in the INCR
594 0583 1 loop below subtracts 2 from the pql$_length value. This is the
595 0584 1 correction value for the unused pql$_listend entry and the true
596 0585 1 ending address of the quota table.
597 0586 1
598 0587 1 Implicit Inputs:
599 0588 1
600 0589 1 The quota list table.
601 0590 1
602 0591 1 Quota table format:
603 0592 1
604 0593 1 31 7 0
605 0594 1 +-----+
606 0595 1 ! name !
607 0596 1 +-----+
608 0597 1 ! cmd line ent desc !
609 0598 1 +-----+
610 0599 1
611 0600 1 Where the name field contains the PQL$_xxx value
612 0601 1 and the cmd line ent desc contains the address
613 0602 1 of the quota name descriptor.
614 0603 1
615 0604 1 Implicit Outputs:
616 0605 1
617 0606 1 The quota list is established.
618 0607 1
619 0608 1 --
620 0609 2 BEGIN
621 0610 2
622 0611 2 LOCAL
623 0612 2 value : volatile; ! Command line entity's value.
624 0613 2
625 0614 2 INCR entry FROM run$a_quota_tbl ! Search through the quota list looking for
626 0615 3 TO run$a_quota_tbl + ((pql$_length - 2) * list_k_entry_size) ! quota info specified in the comman
627 0616 2 BY list_k_entry_size
628 0617 2 DO
629 0618 3 BEGIN ! If we find some, put it into the $CREPRC q
630 0619 3 BIND quota_entry = .entry : $bblock; ! Change reference structure.
631 0620 3 IF CLISPRESNT (.quota_entry [list_l_value]) ! Was this entity in the command line?
632 0621 3 THEN ! Yes...
633 0622 4 BEGIN
634 0623 4 IF .quota_entry [list_b_name] EQL pql$_cpulm ! Is this quota the CPU time limit?
635 0624 4 THEN get_cpulm (.quota_entry [list_l_value], value) ! Yes, special case for CPU time limit...
636 0625 4 ELSE get_value (.quota_entry [list_l_value], value); ! Normal case, just get the value.
637 0626 4 insert_quota (.quota_entry [list_b_name], .value); ! Insert this quota into the quota list.
638 0627 3 END;
639 0628 2 END; ! of DO statement.
640 0629 2
641 0630 2 IF .run$a_quota NEQ 0 ! If any quotas have been processed, be sure

```

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_quotas -- Obtain the process quota values

M 14
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 28
(12)

: 642
: 643
: 644

0631 2 THEN insert_quota (pql\$_listend, 0);
0632 2
0633 1 END; ! of ROUTINE get_quotas

! terminate the list.

		000C 00000 GET_QUOTAS:				
	52	0000'	CF 9E 00002	.WORD	Save R2,R3	: 0575
	53	0000'	CF 9E 00007	MOVAB	RUNSA_QUOTA_TBL, R2	: 0614
			35 10 0000C	MOVAB	RUNSA_QUOTA_TBL+65, R3	: 0615
		01	A2 DD 0000E 1\$:	BSBB	5\$: 0614
00000000G	00		01 FB 00011	PUSHL	1(ENTRY)	: 0620
	25		50 E9 00018	CALLS	#1, CLISPRESNT	
	04		62 91 0001B	BLBC	R0, 4\$	
			0C 12 0001E	CMPB	(ENTRY), #4	: 0623
			5E DD 00020	BNEQ	2\$	
		01	A2 DD 00022	PUSHL	SP	: 0624
0000V	CF		02 FB 00025	PUSHL	1(ENTRY)	
			0A 11 0002A	CALLS	#2, GET_CPULM	
			5E DD 0002C 2\$:	BRB	3\$	
		01	A2 DD 0002E	PUSHL	SP	: 0625
0000V	CF		02 FB 00031	PUSHL	1(ENTRY)	
			6E DD 00036 3\$:	CALLS	#2, GET_VALUE	
	7E		62 9A 00038	PUSHL	VALUE	: 0626
0000V	CF		02 FB 0003B	MOVZBL	(ENTRY), -(SP)	
	52		05 C0 00040 4\$:	CALLS	#2, INSERT_QUOTA	
	53		52 D1 00043 5\$:	ADDL2	#5, ENTRY	: 0614
			C6 15 00046	CMPL	ENTRY, R3	
		0000'	CF D5 00048	BLEQ	1\$	
			07 13 0004C	TSTL	RUNSA_QUOTA	: 0630
			7E 7C 0004E	BEQL	6\$	
0000V	CF		02 FB 00050	CLRQ	-(SP)	: 0631
			04 00055 6\$:	CALLS	#2, INSERT_QUOTA	
				RET		: 0633

; Routine Size: 86 bytes, Routine Base: \$CODE\$ + 0337

: 645 0634 1


```
647 0635 1 %SBTTL 'get_cpulm -- Special case the CPU time limit quota'
648 0636 1 ROUTINE get_cpulm (entry, value) : NOVALUE =
649 0637 1 ++
650 0638 1
651 0639 1 Functional Description:
652 0640 1
653 0641 1 This routine handles the special case of the CPU time limit quota,
654 0642 1 since a simple string to numeric conversion is not the case.
655 0643 1
656 0644 1 We perform the CLI call back locally to get the cpu time limit string,
657 0645 1 then we call the time conversion routine followed by reducing the time
658 0646 1 value to a single longword.
659 0647 1
660 0648 1 Inputs:
661 0649 1
662 0650 1 entry adr Address of the string descriptor for the
663 0651 1 cpu time limit quota command qualifier.
664 0652 1
665 0653 1 Outputs:
666 0654 1
667 0655 1 value adr The address of the resultant time value.
668 0656 1
669 0657 1 Side Effects:
670 0658 1
671 0659 1 If any errors are encountered the will be signalled.
672 0660 1
673 0661 1 --
674 0662 2 BEGIN
675 0663 2
676 0664 2 BUILTIN
677 0665 2 EDIV;
678 0666 2
679 0667 2 LOCAL
680 0668 2 delta : VECTOR [2, LONG],
681 0669 2 psl : $bblock [4];
682 0670 2
683 0671 2 MAP
684 0672 2 entry : REF $bblock,
685 0673 2 value : REF $bblock;
686 0674 2
687 0675 2 CLISGET_VALUE (.entry, run$a_input_desc);
688 0676 3 IF (run$l_status = LIB$CVT_DTIME (run$a_input_desc, delta))
689 0677 2 THEN
690 0678 3 BEGIN
691 0679 3 psl = EDIV (%REF(-200000), delta [0], delta [0], delta [1]);
692 0680 3
693 0681 3 IF .psl [psl$v_v]
694 0682 3 THEN SIGNAL_STOP (run$_illval, 1, run$a_input_desc);
695 0683 3
696 0684 3 IF .delta [1] NEQ 0
697 0685 3 THEN delta [1] = 1;
698 0686 3
699 0687 3 .value = (.delta [0] * 2) + .delta [1];
700 0688 3 END
701 0689 2 ELSE
702 0690 2 SIGNAL_STOP (run$_syntax, 1, run$a_input_desc, .run$l_status);
703 0691 2
```

! Delta time quadword.
! Copy of the processor status longword.

! First we must get the time string and
! convert the .ASCII string to a delta time.
! If conversion was ok then condense the del
! time to a single longword value.
! Convert the delta time to a CPU time limit

! Check for overflow.
! CPU time limit value was too big.

! No overflow...should we round the
! CPU time limit?

! Set the CPU time limit.

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_cpulm -- Special case the CPU time limit qu

B 15
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 30
(13)

; 704

0692 1 END; ! of ROUTINE get_cpulm

				000C 00000 GET_CPULM:							
			53	00000000G	00	9E	00002	.WORD	Save R2,R3		0636
			52	0000	CF	9E	00009	MOVAB	LIB\$STOP, R3		
			5E		08	C2	0000E	MOVAB	RUN\$ INPUT_DESC, R2		
					52	DD	00011	SUBL2	#8, SP		
				04	AC	DD	00013	PUSHL	R2		0675
		00000000G	00		02	FB	00016	PUSHL	ENTRY		
				4004	8F	BB	0001D	CALLS	#2, CLISGET_VALUE		
		00000000G	00		02	FB	00021	PUSHR	#M<R2,SP>		0676
		28	A2		50	D0	00028	CALLS	#2, LIB\$CVT_DTIME		
			30		50	E9	0002C	MOVL	R0, RUN\$ STATUS		
04	AE		6E	FFFCF2C0	8F	7B	0002F	BLBC	R0, 3\$		
					50	DC	00039	EDIV	#-200000, DELTA, DELTA, DELTA+4		0679
			OD		01	E1	0003B	MOVPSL	R0		
					52	DD	0003F	BBC	#1, PSL, 1\$		0681
					01	DD	00041	PUSHL	R2		0682
				00000000G	8F	DD	00043	PUSHL	#1		
			63		03	FB	00049	PUSHL	#RUN\$ ILLVAL		
				04	AE	D5	0004C	CALLS	#3, LIB\$STOP		
					04	13	0004F	TSTL	DELTA+4		0684
					01	D0	00051	BEQL	2\$		
04	AE				6E	D0	00055	MOVL	#1, DELTA+4		0685
					04	BE40	3E	00058	DELTA, R0		0687
					04	0005E		MOVAV	@DELTA+4[R0], @VALUE		
				28	A2	DD	0005F	RET			0676
					52	DD	00062	PUSHL	RUN\$ STATUS		0690
					01	DD	00064	PUSHL	R2		
				00C010FC	8F	DD	00066	PUSHL	#1		
			63		04	FB	0006C	PUSHL	#12587260		
					04	0006F		CALLS	#4, LIB\$STOP		
								RET			0692

; Routine Size: 112 bytes, Routine Base: \$CODE\$ + 038D

; 705

0693 1


```
707 0694 1 %SBTTL 'get_value -- Obtain and convert a command line entity'
708 0695 1 ROUTINE get_value (entry, ret_val) : NOVALUE =
709 0696 1 ++
710 0697 1
711 0698 1 Functional Description:
712 0699 1
713 0700 1 This routine will obtain a command line entity and convert
714 0701 1 the text representation of the value into a numeric quantity.
715 0702 1
716 0703 1 Inputs:
717 0704 1
718 0705 1 entry adr The address of the current command line quota entity
719 0706 1 in the quota table.
720 0707 1
721 0708 1 Outputs:
722 0709 1
723 0710 1 ret_val adr The address of a longword to receive the converted value
724 0711 1 of the command line entity.
725 0712 1
726 0713 1 Side Effects:
727 0714 1
728 0715 1 Errors encountered during conversion will be signalled.
729 0716 1
730 0717 1 --
731 0718 2 BEGIN
732 0719 2
733 0720 2 LOCAL
734 0721 2 value_desc : $bblock [dsc$c_s_bln], ! Descriptor for conversion to a numeric val
735 0722 2 value; ! Resultant value from conversion.
736 0723 2
737 0724 2 MAP
738 0725 2 entry : REF $bblock,
739 0726 2 ret_val : REF $bblock;
740 0727 2
741 0728 2 value_desc [dsc$w_length] = 0; ! Length is left upto the conversion routine
742 0729 2 value_desc [dsc$b_dtype] = dsc$k_dtype_lu; ! Type is unsigned longword.
743 0730 2 value_desc [dsc$b_class] = dsc$k_class_s; ! Scalar.
744 0731 2 value_desc [dsc$a_pointer] = value; ! Address to store result of conversion.
745 0732 2
746 0733 2 IF CLISGET_VALUE (.entry, run$a_input_desc) ! If the entity is present in the command
747 0734 2 THEN ! line and has a value associated with it,
748 0735 3 IF NOT (run$l_status = ! perform the conversion according to the in
749 0736 3 LIB$CVT_DX_DX (run$a_input_desc, value_desc) ! supplied by the descriptors.
750 0737 2 THEN SIGNAL_STOP (run$cvterr, 2, .entry, run$a_input_desc, .run$l_status)
751 0738 2 ELSE .ret_val = .value;
752 0739 2
753 0740 1 END; ! of ROUTINE get_value
INFO#250 L1:0738
Referenced LOCAL symbol VALUE is probably not initialized
```

0004 0000 GET_VALUE:

```
52 0000' CF 9E 00002 .WORD Save R2
MOVAB RUN$a_INPUT_DESC, R2
```

: 0695
:

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_value -- Obtain and convert a command line

D 15
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 32
(14)

04	5E	0C	C2	00007	SUBL2	#12, SP	
08	AE	8F	D0	0000A	MOVL	#17039360, VALUE_DESC	0728
		6E	9E	00012	MOVAB	VALUE, VALUE_DESC+4	0731
		52	DD	00016	PUSHL	R2	0733
		AC	DD	00018	PUSHL	ENTRY	
00000000G	00	02	FB	0001B	CALLS	#2, CLISGET_VALUE	
	2F	50	E9	00022	BLBC	R0, 2\$	
		AE	9F	00025	PUSHAB	VALUE_DESC	0736
		52	DD	00028	PUSHL	R2	
00000000G	00	02	FB	0002A	CALLS	#2, LIBSCVT_DX_DX	
28	A2	50	D0	00031	MOVL	R0, RUNSL_STATUS	
	18	50	E8	00035	BLBS	R0, 1\$	
		A2	DD	00038	PUSHL	RUNSL_STATUS	0737
		52	DD	0003B	PUSHL	R2	
		AC	DD	0003D	PUSHL	ENTRY	
		02	DD	00040	PUSHL	#2	
00000000G	00	8F	DD	00042	PUSHL	#RUNS_CVTERR	
		05	FB	00048	CALLS	#5, LIB\$STOP	
			04	0004F	RET		
08	BC	6E	D0	00050 1\$:	MOVL	VALUE, @RET_VAL	0738
		04	00054 2\$:	RET			0740

; Routine Size: 85 bytes, Routine Base: \$CODE\$ + 03FD

; 754 0741 1


```

756 0742 1 %SBTTL 'insert_quota -- Insert a quota into the quota list'
757 0743 1 ROUTINE insert_quota (name, value) : NOVALUE =
758 0744 1 ++
759 0745 1
760 0746 1 Functional Description:
761 0747 1
762 0748 1 This routine is responsible for entering the specified
763 0749 1 quota list entry into the quota list.
764 0750 1
765 0751 1 Inputs:
766 0752 1
767 0753 1 name val The name of the quota (pql$_xxx)
768 0754 1
769 0755 1 value val The value of the quota.
770 0756 1
771 0757 1 Implicit Outputs:
772 0758 1
773 0759 1 The quota entry has been added to the quota list and
774 0760 1 the list pointer has been updated to point to the next
775 0761 1 entry slot.
776 0762 1
777 0763 1 Side Effects:
778 0764 1
779 0765 1 If this is the first call, we will allocate a heap of
780 0766 1 memory to store the quota list in. This will be
781 0767 1 deallocated at image rundown.
782 0768 1
783 0769 1 --
784 0770 2 BEGIN
785 0771 2
786 0772 2 OWN
787 0773 2 quota_ptr : REF $bblock [4];
788 0774 2
789 0775 2 IF .run$a_quota EQL 0
790 0776 2 THEN
791 0777 3 BEGIN
792 0778 4 IF NOT (run$l_status =
793 0779 4 LIB$GET_VM (%REF(list_k_entry_size * pql$_length),
794 0780 4 run$a_quota))
795 0781 3 THEN
796 0782 3 SIGNAL_STOP (run$_insvirmem, 0, .run$l_status);
797 0783 3
798 0784 3 quota_ptr = .run$a_quota;
799 0785 2 END;
800 0786 2
801 0787 2 quota_ptr [list_b_name] = .name;
802 0788 2 quota_ptr [list_l_value] = .value;
803 0789 2 quota_ptr = .quota_ptr + list_k_entry_size;
804 0790 2
805 0791 1 END; ! of ROUTINE insert_quota

```

Has a quota list been allocated?
No, allocate one...
Call library routine to get virtual memory.
The number of bytes required for the quota list
is computed as the size of a quota list entry
times the number of entries (including the termina
As usual, errors will be sent to the caller.
Point to the first entry in the list.
Set the quota name (pql\$_xxxx).
Set the initial value.
Point to the next quota list entry.

.PSECT \$OWNS,NOEXE,2

001D2 .BLKB 2
001D4 QUOTA_PTR:

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
insert_quota -- Insert a quota into the quota l

F 15

16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 34
(15)

.BLKB 4

.PSECT \$CODE\$,NOWRT,2

				0004 00000 INSERT_QUOTA:				
	52	0000'	CF	9E	00002	.WORD	Save R2	: 0743
	5E		04	C2	00007	MOVAB	RUNSA_QUOTA, R2	:
			62	D5	0000A	SUBL2	#4, SP	:
			2F	12	0000C	TSTL	RUNSA_QUOTA	: 0775
			52	DD	0000E	BNEQ	2\$:
			8F	9A	00010	PUSHL	R2	: 0779
04	AE	4B	AE	9F	00015	MOVZBL	#75, 4(SP)	:
		04	02	FB	00018	PUSHAB	4(SP)	:
00000000G	00		50	DD	0001F	CALLS	#2, LIB\$GET_VM	:
10	A2		50	EB	00023	MOVL	R0, RUNSL_STATUS	:
	12		A2	DD	00026	BLBS	R0, 1\$:
		10	7E	D4	00029	PUSHL	RUNSL_STATUS	: 0782
			8F	DD	0002B	CLRL	-(SP)-	:
		00C012F4	03	FB	00031	PUSHL	#12587764	:
00000000G	00		62	DD	00038	CALLS	#3, LIB\$STOP	:
01A4	C2		C2	DD	0003D	MOVL	RUNSA_QUOTA, QUOTA_PTR	: 0784
	50	01A4	AC	90	00042	MOVL	QUOTA_PTR, R0	: 0787
	60	04	AC	DD	00046	MOVB	NAME, (R0)	:
01	A0	08	05	C0	0004B	MOVL	VALUE, 1(R0)	: 0788
01A4	C2		04	00050	ADDL2	#5, QUOTA_PTR		: 0789
					RET			: 0791

; Routine Size: 81 bytes, Routine Base: \$CODE\$ + 0452

; 806 0792 1


```

808 0793 1 XSBTTL 'get_stsflgs -- Set up initial process state flags'
809 0794 1 ROUTINE get_stsflgs : NOVALUE =
810 0795 1 ++
811 0796 1
812 0797 1 Functional Description:
813 0798 1
814 0799 1 This routine performs call backs to the CLI to obtain the initial
815 0800 1 process state flag settings.
816 0801 1
817 0802 1 Implicit Inputs:
818 0803 1
819 0804 1 run$l_stsflg adr The address of the status flags vector.
820 0805 1
821 0806 1 Implicit Outputs:
822 0807 1
823 0808 1 run$l_stsflg adr The various state flags have been set.
824 0809 1
825 0810 1 Side Effects:
826 0811 1
827 0812 1 Several state flags have been defaulted to false. They are:
828 0813 1 BATCH, INTER, DISAWS and NETWRK.
829 0814 1
830 0815 1 --
831 0816 2 BEGIN
832 0817 2
833 0818 2 run$l_stsflg [prc$vr_ssrwait] = NOT (CLISPRESNT (resource_wait)); ! Resource wait mode.
834 0819 2 run$l_stsflg [prc$vr_ssfexcu] = CLISPRESNT (service_fail); ! System service failure exception mode.
835 0820 2 run$l_stsflg [prc$vr_pswapm] = NOT (CLISPRESNT (swapping)); ! Process swap mode.
836 0821 2 run$l_stsflg [prc$vr_noacct] = NOT (CLISPRESNT (accounting)); ! Process accounting.
837 0822 2 run$l_stsflg [prc$vr_batch] = false; ! Not a batch process.
838 0823 2 run$l_stsflg [prc$vr_inter] = false; ! Not an interactive process.
839 0824 2 run$l_stsflg [prc$vr_hiber] = CLISPRESNT (delay) OR ! Process hibernation state can be set
840 0825 2 CLISPRESNT (interval) OR ! by any combination of the /DELAY,
841 0826 2 CLISPRESNT (schedule); ! /INTERVAL or /SCHEDULE command qualifiers.
842 0827 2 run$l_stsflg [prc$vr_login] = NOT (CLISPRESNT (authorize)); ! Process authorization if image is LOGINOUT
843 0828 2 run$l_stsflg [prc$vr_netwrk] = false; ! Not a network connect object.
844 0829 2 run$l_stsflg [prc$vr_disaws] = false; ! Automatic working set adjustment state.
845 0830 2 run$l_stsflg [prc$vr_imgdmp] = CLISPRESNT (dump); ! Dump requested
846 0831 2 run$l_stsflg [prc$vr_detach] = CLISPRESNT (detach); ! Detached process
847 0832 2
848 0833 1 END; ! of ROUTINE get_stsflgs
```

65

01

```

                                007C 00000 GET_STSFLGS:
                                .WORD Save R2,R3,R4,R5,R6
56 0000* CF 9E 00002 MOVAB RESOURCE_WAIT, R6
55 0000* CF 9E 00007 MOVAB RUN$L_STSFLG, R5
54 00000000G 00 9E 0000C MOVAB CLISPRESNT, R4
                                56 DD 00013 PUSHL R6
64 01 FB 00015 CALLS #1, CLISPRESNT
51 50 D2 00018 MCOML R0, R1
00 51 F0 0001B INSV R1, #0, #1, RUN$L_STSFLG
                                28 A6 9F 00020 PUSHAB SERVICE_FAIL
64 01 FB 00023 CALLS #1, CLISPRESNT
```

0794

0818

0819

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
get_stsflgs -- Set up initial process state

M 15

16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 36
(16)

65	01	01		50	F0	00026	INSV	R0, #1, #1, RUNSL_STSFLG	
			38	A6	9F	0002B	PUSHAB	SWAPPING	0820
		64		01	FB	0002E	CALLS	#1, CLISPRESNT	
		51		50	D2	00031	MCOML	R0, R1	
65	01	02		51	F0	00034	INSV	R1, #2, #1, RUNSL_STSFLG	
			FF14	C6	9F	00039	PUSHAB	ACCOUNTING	0821
		64		01	FB	0003D	CALLS	#1, CLISPRESNT	
		51		50	D2	00040	MCOML	R0, R1	
65	01	03		51	F0	00043	INSV	R1, #3, #1, RUNSL_STSFLG	
		65	0410	8F	AA	00048	BICW2	#1040, RUNSL_STSFLG	0823
			FF38	C6	9F	0004D	PUSHAB	DELAY	0824
		64		01	FB	00051	CALLS	#1, CLISPRESNT	
		53		50	D0	00054	MOVL	R0, R3	
			84	A6	9F	00057	PUSHAB	INTERVAL	0825
		64		01	FB	0005A	CALLS	#1, CLISPRESNT	
		52		50	D0	0005D	MOVL	R0, R2	
		52		53	C8	00060	BISL2	R3, R2	
			10	A6	9F	00063	PUSHAB	SCHEDULE	0826
		64		01	FB	00066	CALLS	#1, CLISPRESNT	
	53	50		52	89	00069	BISB3	R2, R0, R3	
65	01	05		53	F0	0006D	INSV	R3, #5, #1, RUNSL_STSFLG	
			FF28	C6	9F	00072	PUSHAB	AUTHORIZE	0827
		64		01	FB	00076	CALLS	#1, CLISPRESNT	
		51		50	D2	00079	MCOML	R0, R1	
65	01	06		51	F0	0007C	INSV	R1, #6, #1, RUNSL_STSFLG	
		65	0180	8F	AA	00081	BICW2	#384, RUNSL_STSFLG	0829
			FF54	C6	9F	00086	PUSHAB	DUMP	0830
		64		01	FB	0008A	CALLS	#1, CLISPRESNT	
01	A5	01		50	F0	0008D	INSV	R0, #3, #1, RUNSL_STSFLG+1	
		03	FF48	C6	9F	00093	PUSHAB	DETACH	0831
		64		01	FB	00097	CALLS	#1, CLISPRESNT	
01	A5	01		50	F0	0009A	INSV	R0, #1, #1, RUNSL_STSFLG+1	
		01		04	000A0		RET		0833

; Routine Size: 161 bytes, Routine Base: \$CODE\$ + 04A3

; 849 0834 1


```
0835 1 %SBTTL 'schedule_process -- Schedule the process for execution'
0836 1 ROUTINE schedule_process : NOVALUE =
0837 1 ++
0838 1
0839 1 Functional Description:
0840 1
0841 1 This routine is responsible for scheduling wake up request(s) for the
0842 1 created process.
0843 1
0844 1 Implicit Inputs:
0845 1
0846 1 run$l_pid      adr      Address of the created process' PID.
0847 1 run$q_daytim   adr      Address of the wake up time quadword.
0848 1 run$q_interval adr      Address of the repeat time quadword.
0849 1
0850 1 Implicit Outputs:
0851 1
0852 1 The wake up request has been scheduled.
0853 1
0854 1 Side Effects:
0855 1
0856 1 If any error is encountered while attempting to schedule the wake up
0857 1 request(s), we will signal a warning diagnostic to the user and exit.
0858 1
0859 1 --
0860 2 BEGIN
0861 2
0862 2 IF NOT (run$l_status = $SCHDWK (PIDADR = run$l_pid,
0863 2 DAYTIM = run$q_daytim,
0864 2 REPTIM = run$q_interval))
0865 2 THEN
0866 2 SIGNAL (run$_schdwk, 1, .run$l_pid, .run$l_status);
0867 2
0868 1 END; ! of ROUTINE schedule_process
```

! Schedule a wake up for the created process
! At the specified time of day.
! Repeat the scheduled wake up at this inter
! Report any problems scheduling the wake up

.EXTRN SYSSCHDWK

0004 00000 SCHEDULE_PROCESS:

52	0000'	CF	9E	00002	WORD	Save R2	0836
	18	A2	9F	00007	MOVAB	RUN\$L_PID, R2	
	10	A2	9F	0000A	PUSHAB	RUN\$q_INTERVAL	0864
		7E	D4	0000D	PUSHAB	RUN\$q_DAYTIM	
		52	DD	0000F	CLRL	-(SP)	
00000000G	00	04	FB	00011	PUSHL	R2	
04	A2	50	D0	00018	CALLS	#4, SYSSCHDWK	
	12	50	E8	0001C	MOVL	R0, RUN\$L_STATUS	
	7E	62	7D	0001F	BLBS	R0, 1\$	
		01	DD	00022	MOVQ	RUN\$L_PID, -(SP)	0866
		8F	DD	00024	PUSHL	#1	
00000000G	00	04	FB	0002A	PUSHL	#RUN\$ SCHDWK	
		04	00031	1\$:	CALLS	#4, LIB\$SIGNAL	
					RET		0868

; Routine Size: 50 bytes, Routine Base: \$CODE\$ + 0544

RUNDET
V04-000

Run Detached Process -- CLI Utility Procedure
schedule_process -- Schedule the process for ex

J 15
16-Sep-1984 00:27:00
14-Sep-1984 12:08:54

VAX-11 Bliss-32 V4.0-742
[CLIUTL.SRC]RUNDET.B32;1

Page 38
(17)

: 885 0869 1
: 886 0870 1 END ! of MODULE rundet
: 887 0871 0 ELUDOM

.EXTRN LIB\$SIGNAL, LIB\$STOP

PSECT SUMMARY

Name	Bytes	Attributes
\$PLITS	720	NOVEC,NOWRT, RD ,NOEXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)
\$OWNS	472	NOVEC, WRT, RD ,NOEXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)
_LIB\$KEYOS	0	NOVEC,NOWRT, RD , EXE, SHR, LCL, REL, CON, PIC,ALIGN(1)
_LIB\$STATES	10	NOVEC,NOWRT, RD , EXE, SHR, LCL, REL, CON, PIC,ALIGN(1)
\$CODES	1398	NOVEC,NOWRT, RD , EXE,NOSHR, LCL, REL, CON,NOPIC,ALIGN(2)
. ABS .	0	NOVEC,NOWRT,NORD ,NOEXE,NOSHR, LCL, ABS, CON,NOPIC,ALIGN(0)

Library Statistics

File	----- Total	Symbols Loaded	----- Percent	Pages Mapped	Processing Time
_\$255\$DUA28:[SYSLIB]LIB.L32;1	18619	69	0	1000	00:01.8
_\$255\$DUA28:[SYSLIB]TPAMAC.L32;1	42	19	45	14	00:00.2

: Information: 1
: Warnings: 0
: Errors: 0

COMMAND QUALIFIERS

: BLISS/CHECK=(FIELD,INITIAL,OPTIMIZE)/LIS=LISS:RUNDET/OBJ=OBJ\$:RUNDET MSRC\$:RUNDET/UPDATE=(ENH\$:RUNDET)

: Size: 1398 code + 1202 data bytes
: Run Time: 00:26.6
: Elapsed Time: 01:36.1
: Lines/CPU Min: 1966
: Lexemes/CPU-Min: 20041
: Memory Used: 169 pages
: Compilation Complete

0051 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY